

Bedra+Print

8061.01



product
Curtain

description
Floor-to-ceiling curtain+print dim out with a soft sheen

composition
100% flame retardant polyester

width
± 290 cm, ± 114 inches

weight
± 782 gr/m², ± 25 oz/yd¹

visual & thermal comfort
EN 410/EN 14501

Test available
AATCC 148
Test available

flame retardant
NFPA 701 (meth. 1 or 2) , Pass
EN 13773 , Class 1
BS 5867-2 , Type C
NF P 92/503-507 , M1
DIN 4102 , B1
Übereinstimmung , Pass
UNI VF 8456-8457 , Classe 1
CAN/ULC S109 , Pass
IMO 2010 FTP part 7 , Pass

colorfastness crocking

ISO 105-X12
wet 5 (scale 1-5) / dry 5 (scale 1-5)
AATCC 8 (solids)
wet 5 (scale 1-5) / dry 5 (scale 1-5)


colorfastness to light

ISO 105-B02
6 (scale 1-8)
AATCC 16.2 option 1 or 16.3 opt 3
4-5 (scale 1-5)

seam slippage

ASTM D434
warp 43.5 lbs / weft 48 lbs

labels



Baustoffklasse schwerentflammbar
DIN 4102, B1

care




Shrinkage

Shrinkage 30° warp -0.4% / weft -1.4%
Shrinkage 70° warp -2.5% / weft -1.5%

Bedra+Print

8061.01



8061.01