

# Bedra+Print

8061.01



**Product**  
**Curtain**

**Description**  
**Floor-to-ceiling curtain+print dim out with a soft sheen**

**Composition**  
**100% flame retardant polyester**

**Width**  
**± 290 cm, ± 114 inches**

**Weight**  
**± 782 gr/m<sup>2</sup>, ± 25 oz/yd<sup>2</sup>**

**Visual & Thermal comfort**  
**EN 410/EN 14501**

Test available  
**AATCC 148**  
Test available


**Flame retardancy**  
**NFPA 701 (meth. 1 or 2) , Pass**  
**EN 13773 , Class 1**  
**BS 5867-2 , Type C**  
**NF P 92/503-507 , M1**  
**DIN 4102 , B1**  
**Übereinstimmung , Pass**  
**UNI VF 8456-8457 , Classe 1**  
**CAN/ULC S109 , Pass**  
**IMO 2010 FTP part 7 , Pass**

**Colorfastness to crocking**  
**ISO 105-X12**  
wet 5 (scale 1-5) / dry 5 (scale 1-5)  
**AATCC 8 (solids)**  
wet 5 (scale 1-5) / dry 5 (scale 1-5)

**Colorfastness to light**  
**ISO 105-B02**  
6 (scale 1-8)  
**AATCC 16.2 option 1 or 16.3 opt 3**  
4-5 (scale 1-5)

**Seam slippage**  
**ASTM D434**  
warp 43.5 lbs / weft 48 lbs

**Labels**



Baustoffklasse schwerentflammbar  
DIN 4102, B1

**Care & Maintenance**




**Shrinkage**  
Shrinkage 30° warp -0.4% / weft -1.4%  
Shrinkage 70° warp -2.5% / weft -1.5%

# Bedra+Print

8061.01

---



8061.01