

Bedra+Print

8061.01



Produit

Tissus pour rideaux

Description

Rideau imprimable obscurcissant soyeux

Composition

100% polyester ignifuge

Largeur

± 290 cm, ± 114 inches

Poids

± 782 gr/m², ± 25 oz/yd²

Confort Visuel & Thermique

EN 410/EN 14501

Test available

AATCC 148

Test available

Non feu

NFPA 701 (meth. 1 or 2) , Pass

EN 13773 , Class 1

BS 5867-2 , Type C

NF P 92/503-507 , M1

DIN 4102 , B1

Übereinstimmung , Pass

UNI VF 8456-8457 , Classe 1

CAN/ULC S109 , Pass

IMO 2010 FTP part 7 , Pass

Résistance au frottement

ISO 105-X12

wet 5 (scale 1-5) / dry 5 (scale 1-5)

AATCC 8 (solids)

wet 5 (scale 1-5) / dry 5 (scale 1-5)

Solidité lumière

ISO 105-B02

6 (scale 1-8)

AATCC 16.2 option 1 or 16.3 opt 3

4-5 (scale 1-5)

Résistance au glissement à la couture

ASTM D434

warp 43.5 lbs / weft 48 lbs


Étiquettes



USCG -
EU MRA
0038



STANDARD
100
507-0023
Hohenstein HTTI



Vescom B.V.

P-BAY26
170927

Baustoffklasse schwerentflammbar
DIN 4102, B1

Entretien & Maintenance




Rétrécissement

Shrinkage 30° warp -0.4% / weft -1.4%

Shrinkage 70° warp -2.5% / weft -1.5%

Bedra+Print

8061.01



8061.01