

Bray+Print

8065.01



Product
Curtain

Description
Floor-to-ceiling curtain+print black out with an non-directional weave structure

Composition
100% flame retardant polyester acrylic coating

Width
± 280 cm, ± 110 inches

Weight
± 1075 gr/m, ± 35 oz/yd¹

Visual & Thermal comfort
EN 410/EN 14501

Test available
AATCC 148
Test available

Flame retardancy
NFPA 701 (meth. 1 or 2) , Pass
EN 13773 , Class 1
BS 5867-2 , Type B
DIN 4102 , B1
Übereinstimmung , Pass
UNI VF 8456-8457 , Classe 1
CAN/ULC S109 , Pass
IMO 2010 FTP part 7 , Pass

Colorfastness to crocking
ISO 105-X12
wet 4-5 (scale 1-5) / dry 4-5 (scale 1-5)
AATCC 8 (solids)
wet 5 (scale 1-5) / dry 5 (scale 1-5)

Colorfastness to light
ISO 105-B02
5 (scale 1-8)
AATCC 16.2 option 1 or 16.3 opt 3
2.5 (scale 1-5)

Seam slippage
ASTM D434
warp 44 lbs / weft 49.5 lbs

Labels



Baustoffklasse schwerentflammbar
DIN 4102, B1

Care & Maintenance



Shrinkage
Shrinkage 30° warp -0.9% / weft -0.6%
Shrinkage 70° warp -1.5% / weft -1.2%

Bray+Print

8065.01



8065.01