

Bray+Print

8065.01



产品

窗帘

描述

无方向性纺织结构的无缝全遮光curtain+print窗帘面料

成分

100% flame retardant polyester acrylic coating

宽幅

± 280 cm, ± 110 inches

重量

± 1075 gr/m², ± 35 oz/yd¹

视觉及热舒适控制

EN 410/EN 14501

Test available

AATCC 148

Test available

阻燃

NFPA 701 (meth. 1 or 2) , Pass

EN 13773 , Class 1

BS 5867-2 , Type B

DIN 4102 , B1

Übereinstimmung , Pass

UNI VF 8456-8457 , Classe 1

CAN/ULC S109 , Pass

IMO 2010 FTP part 7 , Pass

耐摩擦褪色

ISO 105-X12

wet 4-5 (scale 1-5) / dry 4-5 (scale 1-5)

AATCC 8 (solids)

wet 5 (scale 1-5) / dry 5 (scale 1-5)

耐光照褪色

ISO 105-B02

5 (scale 1-8)

AATCC 16.2 option 1 or 16.3 opt 3

2.5 (scale 1-5)

耐滑缝


ASTM D434

warp 44 lbs / weft 49.5 lbs

标签



USCG -
EU MRA
0038



Baustoffklasse schwerentflammbar
DIN 4102, B1

保养与维护



收缩率

Shrinkage 30° warp -0.9% / weft -0.6%

Shrinkage 70° warp -1.5% / weft -1.2%

Bray+Print

8065.01



8065.01