

Dikson

7063.01 - 7063.14



product

Upholstery

description

Upholstery fabric with a rich blend of soft chenille yarns

composition

> 40% recycled polyester FR / < 60% polyester FR

width

± 140 cm, ± 55 inches

weight

± 819 gr/m², ± 26 oz/yd¹

flame retardant

EN 1021/1-2 , Pass

BS 5852 , Crib 5

NF P 92/503-507 or NF D 60-013 , M1

DIN 4102 , B1

Cal TB 117-2013, section 1 , Pass

IMO 2010 FTP part 8 , Pass

NFPA 260 , Class 1

colorfastness crocking

ISO 105 X12

wet 4-5 (scale 1-5) / dry 4-5 (scale 1-5)

AATCC 8

wet 4 (scale 1-5) / dry 4 (scale 1-5)

colorfastness to light

ISO 105 B02

6 (scale 1-8)

AATCC 16.2 opt.1 or 16.3 opt. 3

4.5 (scale 1-5)

seam slippage

ISO 13936-2

warp 2 mm / weft 2 mm

ASTM D4034

warp 89 lbs / weft 96 lbs

labels



USCG -
EU MRA
0038



STANDARD
100
507-0023
Hohenstein HTTI

care




Shrinkage

Shrinkage 30° - warp -2.6%


Shrinkage 30° - weft -1.9%

Dikson


7063.01 - 7063.14




7063.01




7063.02




7063.03




7063.04




7063.05




7063.06



7063.07




7063.08




7063.09




7063.10




7063.11



7063.12



7063.13



7063.14