

Dolin

8048.01 - 8048.09



Product
Curtain

Description
Light textured blend

Composition
100% flame retardant polyester

Width
± 140 cm, ± 55 inches

Weight
± 407 gr/m², ± 13 oz/yd¹

Sound absorption
ISO 354, alpha w
0.85 (pleated)

Visual & Thermal comfort
EN 410/EN 14501
Test available


Flame retardancy
NFPA 701 (meth. 1 or 2) , Pass
EN 13773 , Class 1
BS 5867-2 , Type C
NF P 92/503-507 , M1
DIN 4102 , B1
Übereinstimmung , Pass
UNI VF 8456-8457 , Classe 1
CAN/ULC S109 , Pass
IMO 2010 FTP part 7 , Pass

Colorfastness to crocking
ISO 105-X12
wet 4-5 (scale 1-5) / dry 4-5 (scale 1-5)
AATCC 8 (solids)
wet 5 (scale 1-5) / dry 5 (scale 1-5)

Colorfastness to light
ISO 105-B02
6 (scale 1-8)
AATCC 16.2 option 1 or 16.3 opt 3
5 (scale 1-5)

Seam slippage
ISO 13936-2
warp 5.5 mm / weft 4.7 mm
ASTM D434
warp 32 lbs / weft 30 lbs

Labels



Baustoffklasse schwerentflammbar
DIN 4102, B1


Care & Maintenance



Dolin

Shrinkage 30° - warp -2.8%
Shrinkage 30° - weft -1%

Shrinkage 70° - warp -2.8%



8048.01

8048.02

8048.03

8048.04

8048.05

8048.06

8048.07

8048.08

8048.09