

# Ellis

8079.01 - 8079.13



Product  
**Curtain**

Description  
**Soft textured, yarn dyed blend with a non-directional two tonal effect**

Composition  
**100% flame retardant polyester**

Width  
**± 300 cm, ± 118 inches**

Weight  
**± 795 gr/m, ± 26 oz/yd<sup>1</sup>**

Sound absorption  
**ISO 354, alpha w**  
0.80 (pleated)

Visual & Thermal comfort  
**EN 410/EN 14501**  
Test available

Flame retardancy  
**NFPA 701 (meth. 1 or 2) , Pass**  
**EN 13773 , Class 1**  
**BS 5867-2 , Type C**  
**NF P 92/503-507 , M1**  
**DIN 4102 , B1**  
**Übereinstimmung , Pass**  
**UNI VF 8456-8457 , Classe 1**  
**CAN/ULC S109 , Pass**  
**IMO 2010 FTP part 7 , Pass**

Colorfastness to crocking  
**ISO 105-X12**  
wet 4-5 (scale 1-5) / dry 4-5 (scale 1-5)  
**AATCC 8 (solids)**  
wet 5 (scale 1-5) / dry 5 (scale 1-5)

Colorfastness to light  
**ISO 105-B02**  
6 (scale 1-8)  
**AATCC 16.2 option 1 or 16.3 opt 3**  
4.5 (scale 1-5)

Seam slippage  
**ISO 13936-2**  
warp 3.3 mm / weft 3.3 mm  
**ASTM D434**  
warp 47 lbs / weft 47 lbs


Labels



USCG –  
EU MRA  
0038



STANDARD  
100  
507-0023  
Hohenstein HTTI



Baustoffklasse schwerentflammbar  
DIN 4102, B1



# Ellis

Shrinkage

8079.01 - 8079.13  
Shrinkage 70% wsg. -2% / weft -2.9%



**8079.01**



**8079.02**



**8079.03**



**8079.04**



**8079.05**



**8079.06**




**8079.07**



**8079.08**



**8079.09**



**8079.10**



**8079.11**



**8079.12**



**8079.13**