

Ellis

8079.01 - 8079.13



Product
Curtain

Description
Soft textured, yarn dyed blend with a non-directional two tonal effect

Composition
100% flame retardant polyester

Width
± 300 cm, ± 118 inches

Weight
± 795 gr/m, ± 26 oz/yd¹

Sound absorption
ISO 354, alpha w
0.80 (pleated)

Visual & Thermal comfort
EN 410/EN 14501
Test available


Flame retardancy
NFPA 701 (meth. 1 or 2) , Pass
EN 13773 , Class 1
BS 5867-2 , Type C
NF P 92/503-507 , M1
DIN 4102 , B1
Übereinstimmung , Pass
UNI VF 8456-8457 , Classe 1
CAN/ULC S109 , Pass
IMO 2010 FTP part 7 , Pass

Colorfastness to crocking
ISO 105-X12
wet 4-5 (scale 1-5) / dry 4-5 (scale 1-5)
AATCC 8 (solids)
wet 5 (scale 1-5) / dry 5 (scale 1-5)

Colorfastness to light
ISO 105-B02
6 (scale 1-8)
AATCC 16.2 option 1 or 16.3 opt 3
4.5 (scale 1-5)

Seam slippage
ISO 13936-2
warp 3.3 mm / weft 3.3 mm
ASTM D434
warp 47 lbs / weft 47 lbs

Labels



Baustoffklasse schwerentflammbar
DIN 4102, B1

Care & Maintenance



Ellis

Shrinkage
8079.01 - 8079.13
Shrinkage 7.0% / weft -2.9%



8079.01



8079.02




8079.03



8079.04



8079.05



8079.06




8079.07



8079.08



8079.09




8079.10



8079.11



8079.12



8079.13