

Nila+Print

8064.01



Product
Curtain

Description
Matte, unstructured floor-to-ceiling curtain+print black out

Composition
100% flame retardant polyester acrylic coating

Width
± 280 cm, ± 110 inches

Weight
± 778 gr/m², ± 25 oz/yd²

Visual & Thermal comfort
EN 410/EN 14501

Test available
AATCC 148
Test available


Flame retardancy
NFPA 701 (meth. 1 or 2) , Pass
EN 13773 , Class 1
BS 5867-2 , Type B
DIN 4102 , B1
Übereinstimmung , Pass
UNI VF 8456-8457 , Classe 1
CAN/ULC S109 , Pass
IMO 2010 FTP part 7 , Pass

Colorfastness to crocking
ISO 105-X12
wet 4-5 (scale 1-5) / dry 4-5 (scale 1-5)
AATCC 8 (solids)
wet 5 (scale 1-5) / dry 5 (scale 1-5)

Colorfastness to light
ISO 105-B02
5 (scale 1-8)
AATCC 16.2 option 1 or 16.3 opt 3
4.5 (scale 1-5)

Seam slippage
ASTM D434
warp 48 lbs / weft 53 lbs

Labels



Baustoffklasse schwerentflammbar
DIN 4102, B1


Care & Maintenance



Shrinkage
Shrinkage 30° warp -1% / weft -0.5%
Shrinkage 70° warp -1.2% / weft -0.4%

Nila+Print

8064.01



8064.01