

Noss

7058.01 - 7058.24



Product

Upholstery

Description

Woven chenille blended in soft colours

Composition

100% flame retardant polyester

Width

± 140 cm, ± 55 inches

Weight

± 904 gr/m, ± 29 oz/yd¹

Flame retardancy

EN 1021/1-2 , Pass

BS 5852 , Crib 5

NF P 92/503-507 or NF D 60-013 , M1

DIN 4102 , B1

Cal TB 117-2013, section 1 , Pass

IMO 2010 FTP part 8 , Pass

NFPA 260 , Class 1

Colorfastness to crocking

ISO 105 X12

wet 4 - 5 (scale 1-5) / dry 4 - 5 (scale 1-5)

AATCC 8

wet 5 (scale 1-5) / dry 5 (scale 1-5)

Colorfastness to light

ISO 105 B02

6 - 7 (scale 1-8)

AATCC 16.2 opt.1 or 16.3 opt. 3

5 (scale 1-5)

Seam slippage

ISO 13936-2

warp 3.3 mm / weft 3 mm

ASTM D4034

warp 77 lbs / weft 91 lbs

Labels



USCG -
EU MRA
0038



STANDARD
100
507-0023
Hohenstein HTTI

Care & Maintenance



Shrinkage

Shrinkage 30° warp -1.5% / weft -1.7%


Shrinkage 70° warp -1.6% / weft -3%

Noss


7058.01 - 7058.24




7058.01




7058.02




7058.03




7058.04




7058.05




7058.06




7058.07




7058.08



7058.09




7058.10




7058.11




7058.12




7058.13




7058.14




7058.15




7058.16




7058.17




7058.18



7058.19



7058.20




7058.21



7058.22



7058.23



7058.24