

Tula

8081.01 - 8081.16



Product
Curtain

Description
Subtle coloured melange structure in a dry wooly look and feel

Composition
100% flame retardant polyester

Width
± 149 cm, ± 59 inches

Weight
± 395 gr/m², ± 13 oz/yd¹

Sound absorption
ISO 354, alpha w
0.75 (pleated)

Visual & Thermal comfort
EN 410/EN 14501
Test available


Flame retardancy
NFPA 701 (meth. 1 or 2) , Pass
EN 13773 , Class 1
BS 5867-2 , Type C
NF P 92/503-507 , M1
DIN 4102 , B1
Übereinstimmung , Pass
UNI VF 8456-8457 , Classe 1
CAN/ULC S109 , Pass
IMO 2010 FTP part 7 , Pass

Colorfastness to crocking
ISO 105-X12
wet 4-5 (scale 1-5) / dry 4-5 (scale 1-5)
AATCC 8 (solids)
wet 5 (scale 1-5) / dry 5 (scale 1-5)

Colorfastness to light
ISO 105-B02
6 (scale 1-8)
AATCC 16.2 option 1 or 16.3 opt 3
5 (scale 1-5)

Seam slippage
ISO 13936-2
warp 3 mm / weft 4.7 mm
ASTM D434
warp 49 lbs / weft 51 lbs

Labels





Tula

Shrinkage
8081.01 - 8081.16
Shrinkage 70° - warp -2%
Shrinkage 70° - weft -1.6%



8081.01



8081.02



8081.03



8081.04



8081.05



8081.06



8081.07



8081.08



8081.09



8081.10



8081.11




8081.12



8081.13



8081.14



8081.15



8081.16